



ISSN: 2319-6505

Available Online at <http://journalijcar.org>

International Journal of Current Advanced Research
Vol 5, Issue 3, pp 629-632, March 2016

International Journal
of Current Advanced
Research

ISSN: 2319 - 6475

RESEARCH ARTICLE

WIRELESS ZIGBEE NETWORK- CAPACITY CALCULATION AND SECURE
DATA CONVEYANCE USING INDEGREE

Girubanandhini M¹ and Kalaiprasath R^{2*}

^{1,2}Department of CSE, Aksheyaa College of Engineering, Chennai, India

*Department of CSE, BIHER, Bharath University, Chennai, India

ARTICLE INFO

Article History:

Received 16th December, 2015
Received in revised form 24th
January, 2016
Accepted 23rd February, 2016
Published online 28th
March, 2016

Key words:

Mobility robustness, tree
topologies, ZigBee wireless
networks.

ABSTRACT

A tree topology is used to construct a Zigbee networks practices by wireless sensor network for data delivery applications. There are 3 types of nodes in zigbee networks; coordinator, router and mobile end devices. Coordinator performs the initialization and maintenance functions in the network. A router is responsible for routing data between the coordinator and mobile end device. In-order to avoid the delivery failures occurs due to node movements and network topology changes, the existing system collect and analyze data about device movement and gives Zigbee node deployment and tree construction framework, which uses three algorithms ZND(zigbee node deployment), ZCD(zigbee coordinator decision) and ZTC(zigbee tree construction). In the proposed system we improve the data delivery by introducing the capacity calculation. If any two nodes have same number of indegree or out-degree, we select the node with maximum capacity.

© Copy Right, Research Alert, 2016, Academic Journals. All rights reserved.

INTRODUCTION

Wireless sensor networks have been an activeresearch topic for around a decade. The recent release of standards in the field, such as IEEE802.15.4 and ZigBee, brought the technology out of research labs and stimulated the development of numerous commercial products. Although many early sensor networks used proprietary routing algorithms and RF technology, most recent products use standards-based networking and RF solutions. ZigBee tree network with one *coordinator (sink)*, some *routers*, and some *end devices*. Each router is responsible for collecting sensed data from its child routers or end devices and relaying incoming data to the sink. Each router can announce a beacon to start it's a superframe.

Which consists of an *active portion* (called an *active slot*) followed by an *inactive portion*. On receiving its parent router's beacon, a child router/end device has to wake up during the former's active portion and forward its data to the former.

There are many ZigBee applications, such as tour guiding and indoor/ building monitoring systems, require moving objects to be equipped with an end device that is connected to a backbone network for data collection and dissemination [7]–[10]. Another category of applications use ZigBee routers as

roadside units and end devices as in-vehicle units. ZigBee networks provide low data rate and low power.

So this paper focus on the ZigBee cluster tree topology. ZigBee specification uses a small protocol stack and it is used in low power, low data rate and low cost applications. In zigbee specification, when a central server cannot locate a mobile end device, it will trigger a device discovery procedure. During the procedure, the central server simply floods the whole network with messages to locate the displaced end device. However, flooding the network is costly in terms of resources, and during the procedure, the network cannot accommodate multiple instances of rapid node mobility. Thus, we need a more efficient and automatic approach for locating mobile end devices. In many applications, there is a regularity in the mobile end device's movement pattern. Using this regularity, we exploit a routing topology and create a tree structure for sensing the node movements.

To improve the data delivery applications, we exploit the regularity in the node movement and construct a mobility robust tree topology with the property that mobile nodes will move along the constructed data-forwarding path with high probability. Data will reach the target mobile nodes as long as they are within the transmission range of any router on the forwarding path. In other words, we choose the positions of the routers and design the tree topology so that most movements are directed toward the root

of the tree. To achieve our objective, we gather information about node movements in the environment and construct a ZigBee tree topology framework. The framework considers the regularity of the mobility patterns during the construction of the tree and deployment of the routing nodes, and it incorporates an overhearing mechanism for mobile nodes to further improve the data delivery ratio. We also design heuristic and low-complexity algorithms for node deployment and tree construction and analyze their performance in ZigBee networks.

Related Work

In this paper, we focus on solving the mobility problem of data delivery in ZigBee networks while attempting to minimize the network overhead. Many schemes that deal with mobility issues in MANETs and DTNs cannot directly be applied to ZigBee networks; however, they provide hints about how we can exploit the regularity in the mobility of nodes to improve mobility support in the network.

In addition, to date, most research on ZigBee mobility support has focused on data collection applications. The network repair strategy demonstrates the importance of constructing or maintaining a connected network topology, but it increases the overhead when the network is operating; thus, it is not suitable for large networks. By exploiting the end device's historical movement data in our node deployment and tree construction algorithms at the design stage, the operating overhead such as route searching packets and network control messages in many conventional methods are substantially reduced.

System Model

A ZigBee network comprises the following three types of devices: 1) a coordinator; 2) multiple routers; and 3) multiple end devices. The coordinator performs the initialization, maintenance, and control functions in the network. A router is responsible for routing data between the end devices and the coordinator. An end device is not equipped with forwarding capability, and its hardware requirements are minimized to control costs. With the three types of devices, the ZigBee standard supports the following three network topologies: 1) star networks; 2) cluster-tree networks; and 3) mesh networks. In a star network, multiple end devices directly connect to the coordinator, and in a cluster-tree network, routers form clusters with their surrounding devices. Moreover, in cluster tree and mesh networks, the devices communicate with each other in a multihop fashion.




Fig1 ZigBee Cluster Tree

Before a topology is constructed, the following three system configuration parameters must be set: 1) the maximum number of children of a router or the coordinator (Cm); 2) the maximum number of child routers of a router or the coordinator (Rm); and 3) the depth of the network (Lm). Fig. 1 shows a ZigBee cluster-tree topology with the parameters $Cm = 4$, $Rm = 3$, and $Lm = 4$.

The proposed scheme does not impose any associations between the mobile end devices and routers. Instead, a mobile end device simply sends a packet, which is then forwarded to the coordinator through the routers. Upon the reception of a packet from a mobile end device, the router forwards the packet to its parent, as indicated by the tree structure. The location of the mobile end device is recognized by the network and maintained by the coordinator, which identifies the last router that was used to forward the end device's uplink data packets. When a downlink packet is sent to a mobile end device, the coordinator delivers the packet to the last recorded location, i.e., the last router that received the uplink packet from the mobile end device. Upon the reception of the downlink packet, the router simply forwards it to the mobile end device and waits for an acknowledgement message from the end device. If the mobile end device has moved from the last known location, the data delivery fails, and the coordinator starts a search by broadcasting a message that asks for information about the mobile end device's current location. Broadcast operations are expensive in terms of bandwidth and power consumption, particularly when mobile end devices frequently move between different router's region.

The movement patterns of mobile end devices exhibit certain regularity, because there are explicit paths that visitors with mobile end devices follow. We collect and utilize the data about device movements to construct a topology, we form a tree topology that is composed of the coordinator and routers to efficiently deliver downlink packets without frequent location tracking overheads. We call the tree topology a *mobility-robust tree*. The objective is to increase the number of successful data deliveries and thereby reduce the number of broadcasts triggered by the coordinator due to the location changes of the mobile end devices.

A heuristic algorithm is proposed to implement the mobility robust ZigBee tree topology. The algorithm is implemented in three phases: 1) ZigBee node deployment (ZND); 2) ZigBee coordinator decision (ZCD); and 3) ZigBee tree construction (ZTC). ZND determines the number and locations of router nodes. ZCD selects one of the routers as the coordinator. ZTC constructs MRZT based on the deployment in the previous two phases.

Mobility-Robust Zigbee Tree topology Deployment

In this section we describe the details of the heuristic algorithm. The algorithm is implemented in the following three phases: 1) ZigBee node deployment (ZND); 2) ZigBee coordinator decision (ZCD); and 3) ZigBee tree construction (ZTC). The ZND phase determines the number and locations of router nodes, the ZCD phase selects one of the routers as the coordinator, and the ZTC phase constructs an MRZT based on the deployment in the previous two phases

states in the mobile profile M (function **CombineState**). Each state in M has a corresponding vertex in G . Some states are merged into one state if the positions of their corresponding vertices in G are covered by one disk centered at a vertex in Gr . Then, the new mobility profile will comprise the edge-weight function of Gr . In line 3, we check if the root has been selected (function **UserAssignRoot**). If a vertex has been designated as the root, the algorithm is completed and outputs the root vertex pr and the edge-weight function Wr .

ZTC Phase

This section explains the implementation of the ZTC phase.

Algorithm 3

Input: A network graph $Gr = (Vr, Er)$ with Wr and pr , Rm , and Lm

Output: A ZigBee routing tree T

1. Define a tree $T = (VT, ET)$ whose root node is pr
2. **repeat**
3. $Q = \emptyset$
4. **for all** $e(u,v) \in Er, u \notin T, v \in T$ **do**
5. Add $e(u,v)$ to Q
6. **end for**
7. $Sort(Q)$
8. **for all** $e(a,b) \in Q$ **do**
9. **if** $CheckLegal(e(a,b), T, Rm, Lm) = TRUE$ **then**
10. Remove $e(a,b)$ from Q

The algorithm defines a tree and initially takes pr as the root node. The main loop is in lines 2–16, and the tree is constructed in this loop until the number of vertices in Gr is equal to that in T . First, we put into an empty set Q each directed edge whose source vertex is not in T and destination vertex is in T . Then, in line 7 (function **Sort**), the algorithm sorts Q in non-increasing order such that the first element in Q is the edge with the largest weight.

If T is legal, we add the edge $e(a,b)$ to the tree. Finally, the algorithm outputs the tree T . Recall that, for the tree construction, our design rationale is to prefer that the paths of downlink data delivery and end device movement patterns are as close as possible and in reverse direction. To achieve this goal for the simple example, the ZTC algorithm constructs the ZigBee routing tree that includes only the coordinator at first. The edge with the maximum weight among all edges directed at the coordinator will then be selected to be included as part of the tree. Then, the edge with the maximum weight among all remaining edges directed at the tree will be chosen to be included, and so on.

CONCLUSION

Finally this paper proposes a scheme that exploits the regularity in node movements in wireless ZigBee networks. It proposes three algorithms to construct mobility based ZigBee cluster tree topology. The primary objective of the proposed approach is to deploy the routers and construct a tree topology that enables mobile end devices to move with high probability in the direction of the routing paths.

References

1. W. Chung, P. Hsiu, Y. Shih, A. Pang, Y. Huang, and K. Hung, "Mobility robust tree construction in ZigBee wireless networks," in *Proc. IEEE ICC*, 2011.
2. Y. Fan, J. Zhang, and X. Shen, "Mobility-aware multipath forwarding scheme for wireless mesh networks," in *Proc. IEEE WCNC*, 2008, pp. 2337–2342..
3. I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci, "Wireless sensor networks: A survey," *Comput. Netw.*, vol. 38, no. 4, pp. 393–422, Mar. 2002.
4. A. Mainwaring, D. Culler, J. Polastre, R. Szewczyk, and J. Anderson, "Wireless sensor
